Printing date 02/26/2018

# 1 Identification

#### · Product identifier

- Trade name: <u>WAKOL MS 230 Engineered Wood Flooring Adhesive, flexible</u> • Application of the substance / the mixture Adhesives
- · Details of the supplier of the safety data sheet

 Manufacturer/Supplier: Loba-Wakol, LLC
 2401 Whitehall Park Drive/Suite 950 Charlotte, NC 28273, USA info@loba-wakol.com
 +1 704 527 5919

· Information department: Product safety department.

#### • *Emergency telephone number: Emergency CONTACT (24-Hour-Number)*

*Emergency CONTACT (24-Hour-Number)* (*GBK GmbH - Contract ID: 98229*) +1 352 323 3500

# 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH	0	Health = 0
FIRE	1	Fire = 1
	0	Reactivity = 0

#### · Other hazards

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.

• **vPvB**: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Adhesive

· Dangerous components: Void

(Contd. on page 2)



Reviewed on 02/26/2018

Printing date 02/26/2018

Reviewed on 02/26/2018

#### Trade name: WAKOL MS 230 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 1)

#### 4 First-aid measures

- · Description of first aid measures
- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

- Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

· Handling:

- · Precautions for safe handling Use only in well ventilated areas.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from humidity and water.
- · Specific end use(s) No further relevant information available.

(Contd. on page 3)



Printing date 02/26/2018

Color:

· pH-value:


· Odor threshold:

· Odor:

Anspruch verbin

Reviewed on 02/26/2018

Trade name: WAKOL MS 230 Engineered Wood Flooring Adhesive, flexible



Pasty

Light brown

Not determined.

Not determined.

**Odorless** 

US



Printing date 02/26/2018

Reviewed on 02/26/2018

#### Trade name: WAKOL MS 230 Engineered Wood Flooring Adhesive, flexible

Change in condition Melting point/Melting range:Undetermined. 253 °C (487.4 °F)Soiling point/Boiling range:253 °C (487.4 °F)Flash point:>185 °C (>365 °F)Flammability (solid, gaseous):Not applicable.Ignition temperature:375 °C (707 °F)Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:Not determined.Vapor pressure:Not determined.Not determined.Not determined.Vapor densityNot determined.Vapor densityNot determined.Vapor densityNot determined.Solubility in / Miscibility with Water:Not miscible or difficult to mix.	
Boiling point/Boiling range:253 °C (487.4 °F)· Flash point:>185 °C (>365 °F)· Flammability (solid, gaseous):Not applicable.· Ignition temperature:375 °C (707 °F)· Decomposition temperature:Not determined.· Auto igniting:Product is not selfigniting.· Danger of explosion:Product does not present an explosion hazard.· Explosion limits:Not determined.· Upper:Not determined.· Vapor pressure:Not determined.· Vapor gensity at 20 °C (68 °F):1.76 g/cm³ (14.687 lbs/gal) (EN ISO 2811-1)· Relative densityNot determined.· Vapor densityNot determined.· Solubility in / Miscibility with	
<ul> <li>Flammability (solid, gaseous): Not applicable.</li> <li>Ignition temperature: 375 °C (707 °F)</li> <li>Decomposition temperature: Not determined.</li> <li>Auto igniting: Product is not selfigniting.</li> <li>Danger of explosion: Product does not present an explosion hazard.</li> <li>Explosion limits: Not determined.</li> <li>Explosion limits: Not determined.</li> <li>Vapor pressure: Not determined.</li> <li>Vapor pressure: Not determined.</li> <li>Vapor density Not determined.</li> <li>Vapor density Not determined.</li> <li>Solubility in / Miscibility with</li> </ul>	
<ul> <li>Ignition temperature: 375 °C (707 °F)</li> <li>Decomposition temperature: Not determined.</li> <li>Auto igniting: Product is not selfigniting.</li> <li>Danger of explosion: Product does not present an explosion hazard.</li> <li>Explosion limits: Not determined.</li> <li>Upper: Not determined.</li> <li>Vapor pressure: Not determined.</li> <li>Density at 20 °C (68 °F): 1.76 g/cm<sup>3</sup> (14.687 lbs/gal) (EN ISO 2811-1)</li> <li>Relative density Not determined.</li> <li>Vapor density Not determined.</li> <li>Solubility in / Miscibility with</li> </ul>	
<ul> <li>Decomposition temperature: Not determined.</li> <li>Auto igniting: Product is not selfigniting.</li> <li>Danger of explosion: Product does not present an explosion hazard.</li> <li>Explosion limits: Not determined. Upper: Not determined.</li> <li>Vapor pressure: Not determined.</li> <li>Density at 20 °C (68 °F): 1.76 g/cm<sup>3</sup> (14.687 lbs/gal) (EN ISO 2811-1)</li> <li>Relative density Not determined.</li> <li>Vapor density Not determined.</li> <li>Solubility in / Miscibility with</li> </ul>	
<ul> <li>Auto igniting: Product is not selfigniting.</li> <li>Danger of explosion: Product does not present an explosion hazard.</li> <li>Explosion limits:         <ul> <li>Lower: Not determined.</li> <li>Upper: Not determined.</li> <li>Vapor pressure: Not determined.</li> <li>Density at 20 °C (68 °F): 1.76 g/cm<sup>3</sup> (14.687 lbs/gal) (EN ISO 2811-1)</li> <li>Relative density Not determined.</li> <li>Vapor density Not determined.</li> <li>Solubility in / Miscibility with</li> </ul> </li> </ul>	
<ul> <li>Danger of explosion:</li> <li>Product does not present an explosion hazard.</li> <li>Explosion limits:         <ul> <li>Lower:</li> <li>Not determined.</li> <li>Upper:</li> <li>Not determined.</li> </ul> </li> <li>Vapor pressure:</li> <li>Not determined.</li> <li>Density at 20 °C (68 °F):</li> <li>1.76 g/cm<sup>3</sup> (14.687 lbs/gal) (EN ISO 2811-1)</li> <li>Relative density</li> <li>Not determined.</li> <li>Vapor density</li> <li>Not determined.</li> <li>Evaporation rate</li> <li>Solubility in / Miscibility with</li> </ul>	
<ul> <li>Explosion limits: Lower: Vpper: Not determined. Vapor pressure: Not determined. Density at 20 °C (68 °F): Relative density Vapor density Vapor density Vapor density Solubility in / Miscibility with</li> </ul>	
Lower: Upper:Not determined.Vapor pressure:Not determined.· Vapor pressure:Not determined.· Density at 20 °C (68 °F):1.76 g/cm³ (14.687 lbs/gal) (EN ISO 2811-1)· Relative densityNot determined.· Vapor densityNot determined.· Evaporation rateNot determined.· Solubility in / Miscibility with	
Upper:Not determined.Vapor pressure:Not determined.Density at 20 °C (68 °F):1.76 g/cm³ (14.687 lbs/gal) (EN ISO 2811-1)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility withVation of the second s	
· Vapor pressure:Not determined.· Density at 20 °C (68 °F):1.76 g/cm³ (14.687 lbs/gal) (EN ISO 2811-1)· Relative densityNot determined.· Vapor densityNot determined.· Evaporation rateNot determined.· Solubility in / Miscibility withNot determined.	
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> <li>Solubility in / Miscibility with</li> </ul>	
· Relative densityNot determined.· Vapor densityNot determined.· Evaporation rateNot determined.· Solubility in / Miscibility withNot determined.	
• Vapor density     Not determined.       • Evaporation rate     Not determined.       • Solubility in / Miscibility with	
• Evaporation rate     • Solubility in / Miscibility with	
· Solubility in / Miscibility with	
Willier. Normiscipic of afficiant of max.	
• Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
<b>Dynamic at 20 °C (68 °F):</b> 80.000 mPas (ISO 2555)	
Kinematic: Not determined.	
· Solvent content:	
Organic solvents: 0.0 %	
Water:         0.0 %           VOC content:         0.0 %	
0.00 %	
• Other information No further relevant information available.	

#### 10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with strong acids and oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information: Product releases low quantities of methanol during appropriated application.

(Contd. on page 5)

Printing date 02/26/2018

Reviewed on 02/26/2018

#### Trade name: WAKOL MS 230 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 4)

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Based on available data, the classification criteria are not met.
- on the eye: Based on available data, the classification criteria are not met.
- Sensitization: Based on available data, the classification criteria are not met.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### · Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.
- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

(Contd. on page 6)



Printing date 02/26/2018

Reviewed on 02/26/2018

#### Trade name: WAKOL MS 230 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 5)

14 Transport information	
· UN-Number	
· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	Void
· DOT, ADR, ADN, IMDG, IATA · Transport hazard class(es)	Void
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
• Marine pollutant:	No
<ul> <li>Special precautions for user</li> </ul>	Not applicable.
• Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
·DOT	
· Remarks:	not regulated
·ADR	
· Remarks:	not regulated
· IMDG	
· Remarks:	not regulated
·IATA	
· Remarks:	not regulated
· UN "Model Regulation":	Void

# 15 Regulatory information

Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
TSCA (Toxic Substances Control Act):	
All ingredients are listed or are not required to be listed on the TSCA inventory.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
	(Contd. on page



Printing date 02/26/2018

Ansnruch verbing

Reviewed on 02/26/2018

#### Trade name: WAKOL MS 230 Engineered Wood Flooring Adhesive, flexible

(Contd. of page 6)

· New Jersey Right-to-Know List:

1317-65-3 limestone

· <u>New Jersey Special Hazardous Substance List:</u>

None of the ingredients is listed.

• Pennsylvania Right-to-Know List: 1317-65-3 limestone

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void

· Hazard statements Void

· National regulations:

· VOC:

- **VOC (EU)** 0.0 g/l
- VOC (USA): 0.0 g/l / 0.00 lb/gl
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Date of preparation / last revision 02/26/2018 / 4

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit